

TIMBER STATEMENT OF PERFORMANCE

Flametect C-WD+ Fire Retardant Treatment for Timber

This document confirms that Flametect C-WD+ fire retardant treatment products supplied under the order referenced below are intended for the treatment of timber and timber-based materials.

QUANTITY SUPPLIED CAN TREAT UPTO A MAXIMUM TIMBER AREA OF:
3.0 m²

Customer Information

Customer	Joe Bloggs
Company	Example only
Address	1 Example Purpose , Not valid Fictitious , NG1 0NO, United Kingdom
Order Number / Date	#D67 17 April 2026

Products Supplied

Product	Batch / SKU	Quantity Purchased	Equivalent Litres
Flametect CWD+ Clear Flame Retardant for Wood - 750 ml Trigger Spray	Fcwd750	1	0.75 L

Certified Treatment Coverage

Total Quantity Purchased	Maximum Certified Treated Area
0.75 L	3.0 m ²

Maximum certified treated area calculated on the basis that 1 litre treats 4 m².

Independent Fire Test Results

When correctly applied at the rate of 4m² per litre to solid timber/wood of minimum thickness of 12mm, Flametect C-WD+ has been proven to achieve:

Standard	Description	Laboratory	Result
BS EN 13501-1:2018	Reaction to Fire Classification for Building Materials	BTTG & ESL Laboratory	Class B s2 d0
BS 476 Part 7	Surface Spread of Flame	Warrington Fire & BTTG	Class 1
BS 476 Part 6	Fire Propagation	Warrington Fire	Class 0
UL 723 / ASTM E84	Steiner Tunnel Test	UL Laboratory	Pass
BS EN 927-6	Accelerated Weathering Test (NT053 & NT054)	UK Laboratories	EXT

Eco-Sol Due Diligence

Eco-Sol Ltd (www.fireproofspray.co.uk) commissions independent fire performance testing through UKAS accredited laboratories & by other similarly recognised laboratories internationally. Full test reports are available to download from www.fireproofspray.co.uk

Users Due Diligence (to be signed after application)

Users of Eco-Sol products should satisfy themselves that:

1. The product and materials treated are compatible.
2. The supporting test results are relevant to their specific application.
3. This Statement of Performance is acceptable to inspecting authorities.

User / Applicator to sign below

Name / Signature

Date

Verification

